

YORLAB® PORTABLE AUTOCLAVE Model No.: YSL / YSI-401

- As per IS - 8462

Specifications:

- Suitable for general laboratory use as well as for field sterilization of instruments and dressings etc. Dome shaped S.S. lid is provided which seals the autoclave with neoprene joint less gasket.
- The lid is tightened to the body when closed. The working pressure is 1.1 to 1.2 Kg./cm²(15-18PSI).
- The sterilizer is made of S.S. Sheet deep drawn to cylindrical shape. The seamless construction allows no bacteria residue & free from dirt accumulation. It is equipped with dial Pressure Gauge 0-60 PSI, spring loaded Safety Valve, dead weight type Safety Valve and Steam Release Valve.
- The load is held in dressing drums (optional), which is supported on a stand (tripod).
- The autoclave is hydraulically tested at twice the working pressure as per ISI requirement.
- It is fitted with ISI marked heater. Supplied complete with mains plug & cord.



- Suitable to work on 220/230 Volt, single phase, 50 Hz, AC supply.
 - Size : 350 x 300-325 mm
- Optional Accessories :**
- Dressing Drum

YORLAB® PORTABLE AUTOCLAVE WITH SYRINGE RACK Model No.: YSL / YSI-618

Specifications : Elegant, non-electrical, made of thick aluminum/St. Steel seamless sheet.

The equipment is designed to attain a pressure of PSI and is tested with greatest care.

Complete with safety valve, weight value, dial pressure gauge, 2 racks for syringes and with a spare gasket and safety plug

Size : 230(Ø) x 230mm (Depth)
300(Ø) x 300mm (Depth)

