

YORLAB® ANAEROBIC INCUBATOR **Model No.: YSL / YSI-185**

Specifications:

- Equipped with large LCD screen display, high-precision microcomputer control (with timing function), it can accurately and visually reflect the actual temperature inside the incubator, over heating alarm adopted, safe and reliable.
- UV Sterilizer effectively prevent bacterial contamination.
- Switch-control for solenoid valve, it can accurately adjust the flow and input any necessary gas.
- Stainless steel cultivation and operation room, transparent impact-resistant glass front window for easy observation, Latex gloves are comfortable and reliable, easy to use.
- Operation room is equipped with deoxidization catalyst.
- The incubator is designed with a double widen door, it can put more petri dishes.
- Equipped with leakage protection.



MODEL	YSL / YSI-185
Time for creating anaerobic state in sample chamber	< 5 minutes
Time for creating anaerobic state in operation chamber	< 1hr
Anaerobic environment maintenance time	> 12 hrs (when no supply of mixed gas)
Temperature Range	RT+3-60 °C
Temperature Stability	< ±0.3°C
Temperature Uniformity	< ±0.1 °C
Display Resolution	0.1°C
Timing Range	1-9999min
Power Rating	600W
Power Supply	AC 220V,50HZ
Net/Gross Weight (Kg)	240/320
Interior Chamber Size (WxDxH)cm	30x19x29
Operation Chamber Size(WxDxH) cm	82x66x67
Exterior Size (WxDxH) cm	126x73x138