

YORLAB® HIGH SPEED CENTRIFUGE Model No.: YSL / YSPL-738

Specifications:

- The Max speed of YSPL-738 is 16500RPM. It can separate samples rapidly.
- It is portable, safe with multiple rotors for customers to choose.



Technical Parameters

Model	YSPL-738	Noise Level	<65dB (A)
Max. Speed	16500 rpm	Power Supply	AC220V±22V 50/60Hz 5A
Max. RCF	22150 xg	Wattage	400w
Max. Capacity	6 x 50ml	Dimension (W x D x H)	325x420x325mm
Speed Accuracy	±30rpm	Package Dim (W x D x H)	385x640x330mm
Time Setting Range	1min to 99min 59s	Net Weight	20kg

Rotor Options



Max.Speed: 16500rpm
Max.RCF: 18930xg
Rotor Capacity: 12x1.5/2.5ml
Adaptor: (0.5ml)
Adaptor: (0.2ml)

No.1



Max. Speed: 13500rpm
Max. RCF: 12835xg
Rotor Cap.: 12 x 5 ml
Adaptor: (0.5ml)
(1.5ml)

No.2



Max. Speed: 12300rpm
Max. RCF: 15550xg
Rotor Cap.: 12x 10ml
Adaptor: (5ml)
(1.5ml)

No.3



Max. Speed: 11000rpm
Max. RCF: 12840xg
Rotor Capacity: 6x50ml
Adaptor: (30ml), (20ml), (10ml)
(5ml), (1.5ml), (15 ml)
(25ml)

No.4



Max.Speed: 13500rpm
Max.RCF: 18720xg
Rotor Capacity: 6x30ml
adaptor: (10ml)

No.5



Max. Speed: 14000rpm
Max. RCF: 22150xg
Rotor Cap.: 30x 1.5ml
Adaptor: (0.2ml)
(0.5ml)

No.6



Max. Speed: 15000rpm
Max. RCF: 21532xg
Rotor Cap.: 24x 1.5/2.5ml
Adaptor: (0.2ml)
(0.5ml)

No.7



Max. Speed: 13500rpm
Max. RCF: 13800xg
Rotor Cap.: 48x0.5 ml

No.8