

YORLAB[®] FLASH FRONT LOADING STERILIZER Model No.: YSL / YSU-616

Specifications:

- Open-type water tank design, easy to clean.
- LED/LCD display all the details of cycle.
- High density filter.
- Fully automatic processor based control.
- High quality vacuum pump.
- Build-in steam generator.
- Optional Printer
- Over temperature and Over pressure protect.
- Double door safety lock.
- Color : Blue.
- Inner chamber made of St. steel 302/304/316.
- Silicon gasket joint less.
- Elegant & safe door locking.




Real-Time Measured Values
Shows real-time values for temperature & pressure & Time & working state.

Cycle Parameter
Parameter settings for temperature, sterilization time & drying time.

Easy Pad
A user- friendly 4 button keypad enables the user to easily browse through the sterilization cycle program setting and use directories.

2017-04-20 16:28		SETTING	
Pressure: -5 kpa	Temperature: 13.4 °C	Model: Unwrapped: 121°C 110kps	Unwrapped: 134°C 210kps
Model: Unwrapped-121°C/110kpa		Wrapped: 121°C 110kps	Wrapped: 134°C 210kps
State: LD	Cycle: 5	Cotton: 121°C 110kps	Plastic: 121°C 110kps
R-Time:	Time: 6:00:00		
Out-T: 14.8 Ste-T: 15.6		Ster-T: 20	Dry-T: 15
Water1: Normal Water2: Normal		V-count: 01	Brightness: M
Door: Closed Error: Normal		Language: EN	O'Clock: 2017-04-20 16:28



Thermal Printer
OPTIONAL high quality built-in thermal printer for paper printouts

YSL / YSU-616	
Volume	12L
Chamber Size	Ø200x360mm
Display	LCD
Product Size	560x450x410mm
N.W/G.W.	45/49KG
Printer	Optional

YSL / YSU-616	
Volume	18L
Chamber Size	Ø250x350mm
Display	LCD
Product Size	560x450x410mm
N.W/G.W.	48/50KG
Printer	Optional

YSL / YSU-616	
Volume	23L
Chamber Size	Ø250x450mm
Display	LCD
Product Size	680x450x410mm
N.W/G.W.	50/55KG
Printer	Optional

PROG	Unwrapped	Unwrapped	Wrapped	Wrapped	Cotton	Plastic	B&D Test	Vacuum Test
Temp.(°C)	134	121	134	121	121	121	134	105
Pressure(KPA)	210	110	210	110	110	110	210	20
Time (Min.)	4-20	15-30	4-20	15-30	15-30	15-30	3.5	5