

YORLAB® WARMING CABINET **Model No.: YSL / YSI-168**

Specifications:

- Cabinet is designed to raise the temperature of surgical IV and irrigation solutions and/or blankets to an acceptable level for hospital and surgical outpatient center applications.
- **FEATURES**
- Single-Compartment Model features a heating chamber available in two depths: 18" (457 mm) 24" (610 mm) deep.
- Dual-Compartment Model features an upper and lower heating chamber with independent temperature controls, and a choice of two depths: 18" (457 mm) or 24" (610 mm) deep. Key Door Locks feature a key that is used to lock/unlock the door. The key is turned counterclockwise to lock door; clockwise to unlock door.
- **Single Compartment**
- 18" (457mm) deep
- 24" (610mm) deep
- **Dual Compartment**
- 18" (457mm) deep
- 24" (610mm) deep
- **Door Options**
- Glass
- Solid
- **Door Lock Option**
- Electronic Numeric Keypad
- Mobile Base Option
- Mobile base with bumpers and locks



- **Temperature recording option**
- USB Port
- **Voltage**
- 120V
- 220V

Dual-Compartment Model –
Solid Doors (with optional mobile
base)



Single-Compartment Model –
Solid Door

Dual-Compartment Model –
Glass Doors (with optional mobile
base)



Single-Compartment Model –
Glass Door

Construction :

- Freestanding and recessed units ship identically (with outer side, top and back covers). Outer side, top and back covers are removed for recessed installation. When recessed, unit requires a connection to building service (not provided by us).
- The unit contains a heating chamber, instrumentation and operating controls, and a lower heated chamber when dual-compartment model is specified.