

YORLAB® DISINFECTOMAT WASHER DISINFECTOR **Model No.: YSL / YSU-609Ex.**

Specifications:

- Cycle pump with large flux can wash utensils efficiency
- The cycle water can be heated to 90oC and disinfect goods primarily
- 6 washing program automatically
- High efficiency dry performance
- Auto adding detergent
- Intelligent control system
- Auto heating function
- Auto water discharging
- Safety door device with chain control
- Temperature insulate
- Washing chart with large volume (Optional)
- Designed with large storage surface. An excellent complement to the existing installation.
- Takes over the connection of existing old appliances and can be extended by means of accessories such as Bed Pan and Urine Bottle shelves to complete the hospital cleaning center.
- Most suitable for emptying, cleaning and disinfector care utensils such as Bed Pan urine bottle, commode buckets, receptacles etc. All Technical parameters are same as YSU-609 but with Double.

High Impact Cleaning System:

- The Disinfector is provided with three rotary spray arms. The design and location of the arms ensure that every surface of the load is uniformly cleaned. The unit is constructed with out any angles in order to prevent dirty breeding grounds.
- The rotation of the arm is activated by the water pressure which eliminates any mechanical drive system

Inbuilt Disinfection System:

- The unit is incorporated with an in-built electric water heater. The hot water here is used to disinfect the load at a temperature of 90°C (i.e. hemodisinfection) after thorough cleaning and rinsing.

Flexible Loading System:

- Stericlean Disinfector comes with a range of standard accessories for different surgical appliance & Kidney Trays, Bottles, Tubings and instruments.
- Additional loading cassettes are available as optional

Automatic Detergent Dozing:

- The machine is incorporated with an automatic detergent dozing system to doze the required amount of detergent in the rinse water

User Friendly Program Menu:

- The Disinfector has a Microprocessor Controlled operating system.



- The operating Console is provided with a membrane key pad and electronic display unit of easy operation and monitoring of the process.
- Up to 3 pre-programmed processes give the user fantastic flexibility for cleaning and disinfecting a wide range of load configurations

In-Built Heating System:

- In Hospitals where hot water is not available the Disinfector is equipped with an electric heating system. This heats the water to a temperature of 90°C for higher cleaning efficiency.

Fully Sanitary Construction:

- The body is fabricated from non-corrosive 304 Grade Stainless Steel with high quality argon welding.
- All corners are rounded for easy cleaning and to avoid contamination.
- The door is provided with a food grade silicone gasket. All piping and valves are of stainless steel construction with silicon seals.

Installation:

- The Disinfector is available in both single door and double door options to suit different CSSD configurations and requirements.
- The machine requires no installation.
- It has to be connected to the different supply lines and drain to start operation